

LED - SITE SAFETY LIGHT

SIDE MOUNT



Strong, Durable



Up To 925 Hours



Cost - Effective



Zero Dimming



**1 YEAR
LIMITED
WARRANTY**

Installation



Available in amber, red, or white lenses.

This right-angle safety light is designed for versatile installation and can be securely mounted to all types of scaffolding as well as a wide range of construction equipment using its adaptable mounting bracket.

By removing half of the bracket, the unit can also be directly screwed or bolted onto flat surfaces, providing additional installation flexibility.

Versatility



Durable Safety Lights for Scaffolding and Construction Areas

Engineered for demanding job sites, these safety lights feature a robust, impact-resistant design built to withstand harsh environmental conditions.

Ideal for use on barriers, skip lugs, scaffolding, and Heras fencing, they provide reliable visibility and enhanced site safety across a wide range of applications.

V2 Performance



Maximum Visibility - Zero Compromise

The new V2 PCB delivers a 40% increase in total illumination. By optimising light distribution across a wider arc, we have eliminated narrow beams in favour of superior localised clarity.



Consistent Performance

Forget the "dimming effect" of traditional battery-powered units. Our integrated Battery Boost technology ensures:

- Uniform Output: High-intensity brightness maintained throughout the entire operating cycle.
- Total Reliability: No fading performance as batteries deplete.
- Safety Assurance: Elimination of dangerous "grey areas" caused by failing light levels.



Brighter Illumination with New Motion Mode

Now equipped with additional LEDs for greater brightness, plus a new motion-sequencing mode for enhanced performance and visual effect. The 360 degree lenses provide flashing visibility for up to 925 hours.

Low-Battery Indicator

The light gently flickers when the batteries are running low, letting you know it's time to replace them.

Specification

Weight	Size	Power	Modes	Flash Pattern	Ing. Protection	Operating Temp.
255g	120 x 118 x 95mm	2 x AA Alkaline Batteries	Flashing, Motion, Steady	300 Milliseconds	IP 54	-15°C to +45°C



Packing Info

Model	Inner Box Dimensions	Carton Dimensions	G.W. Light	G.W. Carton	QTY per Carton
SBL Y - 1403 BHYR - 1405 BHYW - 1405	135 x 124 x 100mm	510 x 430 x 300mm	0.255 KG	11.95 KG	32



* PLEASE READ ALL INTRUCTIONS BEFORE USE *

WARNING

* DO NOT SUBMERGE IN WATER *



www.whisafeguard.com